

MAKO NEWS

The Violet CTP Platesetter with high-quality color for small and medium-sized newspapers

Making plates in any newspaper needs to be fast and simple, and **MAKO NEWS** sets the winning pace. Its flexible format combined with fast, easy operation is ideally suited to deadline-driven publishing environments where dependable quality output is essential.

- Simple operation – just queue a single, paired or doubletruck page, position the plate against the integrated edge-register pinbar. The MAKO NEWS will do the rest.
- Over 78 Berliner plates per hour throughput at 1200 dpi without complex load/unload cycles.

- Accommodates the most popular range of web widths up to a maximum format of 635mm x 960mm (25.0" x 37.8").
- Ideal for all popular single-width newspaper presses from Berliner to the Goss Community.
- To provide added flexibility, the optical configuration includes eight resolutions from 1016 to 2540 dpi and three anamorphic resolution sets (1016 x 2032 dpi, 1200 x 2400 dpi, and 1270 x 2540 dpi).
- Small footprint allows ease of installation.
- Open-ended software system accepts 1-bit TIFF files – choose the solutions you want. ECRM is here to help.
- No hidden extras – our online conveyor is standard on all MAKO CTP, allowing for a direct connection to the processor at no extra cost.
- Basic electricity requirements and quick installation – no dedicated power line needed (power conditioner supplied). Low energy consumption, draws the same energy as a PC.
- Simple and intuitive operator interface makes training easy for everyone.



Choose ECRM for your Violet CTP solutions

ECRM products offer the lowest total cost of ownership in the business and the highest quality performance in the industry. Our manufacturing facility is located in Tewksbury, Massachusetts, USA and is certified as being in conformity to ISO 9001:2000 standards. Our signature flexible design lets you decide what's best for your CTP system, workflow, plates and processors. We support you every step of the way and work with you to ensure complete system integrity.



MAKO NEWS Specifications

Plate Sizes	Maximum: 635mm x 960mm (25.0" x 37.8") Minimum: 228mm x 252mm (8.9" x 9.9")
Plate Thickness	0.14mm to 0.35mm (0.0055" to 0.014")
Media Types	Violet-sensitive photopolymer and silver halide metal plates. See media specifications for safe-light information.
Recording Source	Violet laser diode (405 nm), available for photopolymer or silver halide plates
Maximum Line Screen	Up to 150 lpi. Media dependent
Resolutions	8 resolutions from 1016 to 2540 dpi. Three anamorphic resolution sets available -- 1016 x 2032, 1200 x 2400 and 1270 x 2540.
Image Scaling	Image scaling from 85% to 110% of original
Repeatability	0.025mm (0.001") typical May vary according to media type and processing conditions
Processing	Online: The plate transport automatically moves the plate into the processor.
Environmental	Power: 100 - 240 Volts; 3 Amps; 250 watts maximum; 50/60Hz, single phase Heat Dissipation: 850 BTU/hour
Operating Conditions	62 - 86° F (17 - 30° C); relative humidity 45 - 65%, non-condensing. Relative humidity outside of this range may affect performance. Operating conditions outside plate media specifications may affect performance.
Weight	145.5 kg (320 lbs.)
Footprint Dimensions	Width: 96.5cm (38.0") Length: 185.4cm (73.0") Height: 188.0cm (74.0")

ECRM[®]
imaging systems

Headquarters:

554 Clark Road
Tewksbury, MA 01876
USA
Tel: (+1) 978.851.0207
Fax: (+1) 978.851.7016
sales@ecrm.com
www.ecrm.com

International Sales Offices:

3 Century Court, Tolpits Lane
Watford, Hertfordshire
WD18 9PU, UK
Tel: (+44) 1923.218.255
Fax: (+44) 1923.218.256
sales_uk@ecrm.com

B2, 10/F, Block B,
Kailey Industrial Centre,
12 Fung Yip Street,
Chai Wan, Hong Kong
Tel: (+852) 2564-8989
Fax: (+852) 2564-8821
sales_hk@ecrm.com
sales_asia@ecrm.com

All ECRM products carry the CE mark. All products are CSA & CSA/NRTL Certified. Class 1 Laser Products ECRM's Tewksbury facility is ISO 9001:2000 certified.

All trademarks are the property of their respective owners and their use in this documentation is acknowledged and recognized. The information provided in this document is subject to change without notice.

