

# MAKO NEWSmatic

Replaces aging imagesetting technology with automated Violet CTP production at an affordable price

The fully automated **MAKO NEWSmatic** provides new levels of simplicity, versatility and economy and is the ideal transition to unattended CTP production for newspapers.

- Features a straight-through plate path with no complex load/unload cycle.
- Ideal for all popular single-width newspaper presses from Berliner to the Goss Community.
- 60 broadsheet plates per hour at 1270 dpi.
- Accommodates the widest range of web widths up to a maximum format of 635mm x 927mm (25" x 36.5").
- ECRM's patented FleXarm slip sheet removal system makes automation a realistic possibility for smaller and medium-sized printers.

- Sensors track slip-sheets through pick-up, removal and disposal - ensuring fast throughput and superior reliability
- Operates in normal daylight conditions
- No hidden extras – our online conveyor is standard on all MAKO CTP, allowing for a direct connection to the processor at no extra cost.
- Open-ended software system accepts 1-bit TIFF files – choose the solutions you want. ECRM is here to help.
- To provide added flexibility, the optical configuration includes eight resolutions from 1016 to 2540 dpi and three anamorphic resolution sets (1016 x 2032 dpi, 1200 x 2400 dpi, and 1270 x 2540 dpi).
- Optional high capacity plate cassette and trolley handles 340 eight gauge (0.2mm) plates or 250 twelve gauge (0.3mm) plates.
- Basic electricity requirements and quick installation – no dedicated power line needed. Low energy consumption, draws the same energy as a PC.
- Simple and intuitive operator interface makes training easy for everyone.



# Choose ECRM for your Violet CTP solutions

ECRM products offer the lowest total cost of ownership in the business and the highest quality performance in the industry. Our manufacturing facility is located in Tewksbury, Massachusetts, USA and is certified as being in conformity to ISO 9001:2000 standards. Our signature flexible design lets you decide what's best for your CTP system, workflow, plates and processors. We support you every step of the way and work with you to ensure complete system integrity.



## MAKO NEWSmatic Specifications

|                                |  |
|--------------------------------|--|
| <b>Plate Sizes</b>             | Maximum: 635mm x 927mm (25.0" x 36.5") Minimum: 385mm x 289.6mm (15.15" x 11.4")   |
| <b>Plate Thickness</b>         | 0.14mm to 0.35mm (0.0055" to 0.014")   |
| <b>Media Types</b>             | Violet-sensitive photopolymer and silver halide metal plates. See media specifications for safe-light information.   |
| <b>Plate Cassette Capacity</b> | High capacity cassette: 340 plates - 8 gauge (0.2mm); 250 plates - 12 gauge (0.3mm)<br>Standard cassette: 65 plates - 8 gauge (0.2mm); 58 plates - 12 gauge (0.3mm)  |
| <b>Recording Source</b>        | Violet laser diode (405 nm), available for photopolymer or silver halide plates  |
| <b>Maximum Line Screen</b>     | Up to 150 lpi. Media dependent   |
| <b>Resolutions</b>             | 8 resolutions from 1016 to 2540 dpi. Three anamorphic resolution sets available — 1016 x 2032, 1200 x 2400 and 1270 x 2540.  |
| <b>Image Scaling</b>           | Image scaling from 85% to 110% of original   |
| <b>Repeatability</b>           | 0.025mm (0.001") typical<br>May vary according to media type and processing conditions   |
| <b>Air Supply Requirement</b>  | 6.2 BAR @ 283L/min (10CFM @ 90 PSI) (Required for slip sheet removal option)   |
| <b>Processing</b>              | Online: The plate transport automatically moves the plate into the processor.  |
| <b>Environmental</b>           | Power: 100 - 240 Volts; 3 Amps; 250 watts maximum; 50/60Hz, single phase<br>Heat Dissipation: 850 BTU/hour   |
| <b>Operating Conditions</b>    | 62 - 86° F (17 - 30° C); relative humidity 45 - 65%, non-condensing. Relative humidity outside of this range may affect performance. Operating conditions outside plate media specifications may affect performance. |
| <b>Weight</b>                  | 409 kg (900 lbs.)  |
| <b>Footprint Dimensions</b>    | Width: 86.5cm (34.0") Length: 336.0cm (132.6") Height: 191.0cm (75.1")   |

**ECRM**<sup>®</sup>  
imaging systems

### Headquarters:

554 Clark Road  
Tewksbury, MA 01876  
USA  
Tel: (+1) 978.851.0207  
Fax: (+1) 978.851.7016  
sales@ecrm.com  
[www.ecrm.com](http://www.ecrm.com)

### International Sales Offices:

|  |   |
|--|---|
| 3 Century Court, Tolpits Lane<br>Watford, Hertfordshire<br>WD18 9PU, UK<br>Tel: (+44) 1923.218.255<br>Fax: (+44) 1923.218.256<br>sales_uk@ecrm.com | B2, 10/F, Block B,<br>Kailey Industrial Centre,<br>12 Fung Yip Street,<br>Chai Wan, Hong Kong<br>Tel: (+852) 2564-8989<br>Fax: (+852) 2564-8821<br>sales_hk@ecrm.com<br>sales_asia@ecrm.com |
|--|---|

All ECRM products carry the CE mark. All products are CSA & CSA/NRTL Certified. Class 1 Laser Products ECRM's Tewksbury facility is ISO 9001:2000 certified.

All trademarks are the property of their respective owners and their use in this documentation is acknowledged and recognized. The information provided in this document is subject to change without notice.

